

AirBORNE™

750i Transport Incubator

Gentle ride
in-house transport



Meets new NRP guidelines
Integrated pulse oximetry option
Light, compact, easy to maneuver
Gentle-ride shock absorbers

Technical Specifications

Standard Features	Large double-wall chamber with 360° visibility Head and front access doors 2 hand ports on front door 2 hand ports on back of infant chamber 5 accessory ports for IV/respiratory tubing Slide out intubation tray Pressure diffusing mattress LED light bar Extended-life battery Skin temperature probe	Large LED display Humidification reservoir IV pole 2 pairs of infant restraint straps 2 'D' or 2 'E' cylinder mounts Mobile cart with 2 storage shelves Large 5 inch casters, two with brakes 4 anti-vibration shock absorbers 6 medical grade A/C outlets (N. America only) Power cord wrap
Audible and Visual Alarms	System failure Temp sensor failure Air flow failure AC failure	Power failure High temp Low battery
Visual Indicators	Set air temp Set temp >37°C Air temp Baby temp Battery life	Battery power Battery charging AC power DC power
Dimensions	48.25 in. H x 24.0 in. W x 50.0 in. L (122.5 cm H x 61 cm W x 127.0 cm L), w cart, w/o IV pole or light bar	
Weight	166.6 lb (75.52 kg), w cart, w/o overhead shelf	
AC Power	115V AC, 50-400 Hz, 230V AC, 50-400 Hz	
External DC Power	12V DC, 10A maximum	
Internal Battery	One 12V 26-amp-hour sealed lead/acid type with auto recharge	
Digital Air Temperature Control	17.0°C to 38.9°C range, 0.1°C increments, Display resolution 0.1°C	
Sound Level	<60 dB	

Additional Options Available

Integrated Pulse Oximetry	Masimo® or Nellcor™, and O ₂ Analyzer with audible and visual alarms	
Airway Management	Air and O ₂ check valves (wall and cylinders) O ₂ blender (no bleed low flow) and 0-16 lpm flowmeter 1 air, 1 O ₂ regulator with Ohmeda style quick connects 1 air and 1 O ₂ supply hose (cylinder to incubator)	Air and O ₂ on/off valves (cylinders) 1 air, 1 O ₂ Ohmeda style quick connect 1 air, 1 O ₂ coily hose (incubator to wall)
Conventional Ventilator	Neonatal transport ventilator with remote vent outputs	
Electric Suction	Portable, battery-powered suction	
Patient Monitor	Install hospital-supplied monitor or one provided by International Biomedical	
Thermal/Privacy Cover		
Resuscitation	Disposable resuscitation bag and mask	T-piece resuscitation
Shelves/Mounts	Overhead shelf and/or side platforms Mounting posts 1 in. diameter x 5 in., and 1 in. x 7 in.	Enclosed bottom shelf

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. 512.873.0033 F. 512.873.9090


int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.

UK

SLE Ltd

Twin Bridges Business Park, 232 Selsdon Road, South Croydon
Surrey, CR2 6PL
T. 020 8681 1414 F. 0208 649 8570
Web: www.sle.co.uk E: pneilson@sle.co.uk



IB 2012 04 016 AB004-11/2012